

# Technical Datasheet

EN ISO 13485 certified	
<b>Article - No:</b>	<b>02-352-6000</b>
<b>Revision:</b>	<b>4</b>
<b>Remarks</b>	<b>single use only</b>

## Specification

<b>Product</b>	Test tube PP with fitted screw cap PE, 12ml, Ø16x100 mm, round bottom, tube transparent, cap natural, grad., sterile R, max. RCF 4.000g, Autocl. up to 121°C (no cap)
<b>Dimensions</b>	outer diameter: 16,00 mm (+/- 0,2 mm) height (without screw cap): 100,00 mm (+/- 0,2 mm)
<b>Colour</b>	tube transparent, cap natural
<b>Graduation</b>	grad.
<b>Nominal Capacity</b>	12ml
<b>Material Characteristics</b>	tube: polypropylene (PP) cap: polyethylene (PE)
<b>Temperature range</b>	tube: -196°C up to +121°C cap: -50°C up to +80°C
<b>Autoclavability</b>	Autocl. up to 121°C (no cap)
<b>Centrifugation</b>	max. RCF 4.000g
<b>Product Characteristics</b>	biologically inert physiologically harmless no heavy metals according to EC/94/62
<b>Purity Grade</b>	do not contain any pyrogens
<b>Sterilisation Process</b>	radiation sterilization SAL 10-6
<b>Shelf - Life</b>	36 months at controlled storage conditions
<b>Packaging</b>	pcs per bag: 100 pcs per carton: 1.000 pcs per pallet: 24.000
<b>Storage</b>	dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +10°C to max. +30°C pal. not stackable
<b>Approved by nerbe plus quality department</b>	